

PresentationPRO-II

PresentationPRO-II simplifies presentations, live events,
corporate boardrooms, and church services.



PRODUCT SPECIFICATIONS**PRESENTATIONPRO-II****Scaled Video Channel Inputs**

Input Types	<ul style="list-style-type: none">■ Analog Inputs (8) - RGBHV/RGBS/RGB computer video, YPbPr video (SD or HD), S-video, or Composite video on 15-pin HD connectorSDI Input (1) - per SMPTE 259M-C on BNC connector (PresentationPRO-II Digital Only)
--------------------	---

Input resolutions	<ul style="list-style-type: none">■ PAL or NTSCComputer Resolutions VGA (640 x 480) through UXGA (1600 x 1200)HDTV Resolutions up to 1920 x 1080 (720p, 1080i, 1080p)Plasma Display Resolutions
--------------------------	--

Unscaled Background /Key Channel Input (Optional)

Input Types	DVI Digital Input -per DDWG 1.0 on DVI-I connector
--------------------	--

Input resolutions	Resolution must be same as selected output resolution.
--------------------------	--

Outputs

Output Types	<ul style="list-style-type: none">■ Analog Output - RGBHV/RGBS/RGB (non-interlaced only) on 15-pin HD connectorsDVI Digital Output - per DDWG 1.0 on DVI-I connector
---------------------	---

Output Resolutions	<ul style="list-style-type: none">■ Computer Resolutions VGA (640 x 480) through UXGA (1600 x 1200)HDTV Resolutions, progressive up to 1920 x 1080(1080p)Plasma Display Resolutions
---------------------------	---

User Control

Front Panel Control	LCD TouchScreen Display, Keyboard circuitry, Rotary Encoders and LED lighted push buttons
----------------------------	---

Remote control	<p>The unit may be controlled from a computer or external controller via LAN or an RS-232 serial link.</p> <p>Control functions include:</p> <ul style="list-style-type: none">■ Source Input ConfigurationOutput Format SelectionTest Pattern SelectionVideo Source SelectionTransition Effect Selection
-----------------------	---

Last updated: 21 Jan 2018

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.